

# PQ CORES

| Part No. | Core    | A<br>mm                            | B<br>mm                            | C<br>mm                         | D<br>mm                          | E<br>mm              | F<br>mm                           | G<br>mm                            | le<br>mm <sup>2</sup> | Ae<br>mm <sup>2</sup> | Ve<br>mm <sup>3</sup> | F48                               | F49                               |
|----------|---------|------------------------------------|------------------------------------|---------------------------------|----------------------------------|----------------------|-----------------------------------|------------------------------------|-----------------------|-----------------------|-----------------------|-----------------------------------|-----------------------------------|
| 29-060-  | PQ26x20 | 27.3 <sup>+0.46</sup> <sub>-</sub> | 22.5 <sup>+0.46</sup> <sub>-</sub> | 12 <sup>+0.2</sup> <sub>-</sub> | 19 <sup>+0.45</sup> <sub>-</sub> | 15.50 <sup>Min</sup> | 11.5 <sup>+0.3</sup> <sub>-</sub> | 20.2 <sup>+0.25</sup> <sub>-</sub> | 45                    | 121                   | 5470                  | -                                 | 3000 <sup>+25%</sup> <sub>-</sub> |
| 29-070-  | PQ26x25 | 27.3 <sup>+0.46</sup> <sub>-</sub> | 22.5 <sup>+0.46</sup> <sub>-</sub> | 12 <sup>+0.2</sup> <sub>-</sub> | 19 <sup>+0.45</sup> <sub>-</sub> | 15.50 <sup>Min</sup> | 16.1 <sup>+0.3</sup> <sub>-</sub> | 24.7 <sup>+0.25</sup> <sub>-</sub> | 54.30                 | 120                   | 6530                  | 5250 <sup>+25%</sup> <sub>-</sub> | 2500 <sup>+25%</sup> <sub>-</sub> |

❖ Gapped values can be provided on request.

❖ All above Cores available in other materials on request.